



TANK SPECIFICATIONS

1) TANK MATERIAL: ALUMINUM OTHER: _____

2) COMPARTMENTS:	1	2	3	4	5	TOTAL *
	900	900	900			2700

3) METAL: BOTTOM 0.313 TOP 0.190, SIDES 0.190, HEADS 0.190

4) BULKHEADS: SINGLE DOUBLE:

5) CANOPY: STD 42" (SINGLE) 52" DUAL METER AND/OR REELS
 STD FULL REAR BULKHEAD "BIKINI" STYLE 2/3 REAR BULKHEAD

6) BOTTOM LOAD/VAPOR RECOVERY: FULLY CAPPED NONE
(SEE PAGE 2 FOR DETAILS)
INSTALLED WITH 2" CAMLOCK WITH BUTTERFLY D-10

7) PROPOSED BULKHEAD SIZE: 61"x92" OVERALL TANK LENGTH (INCLUDING CANOPY 175"

8) HOSE TROUGH/TUBE: NONE OTHER: DRIVERSIDE 6" TUBE ENCLOSED

**NOTE: All KME tanks are manufactured at our U-Stamp Certified, DOT Registered world headquarters. They are built to meet or exceed all DOT 406 standards and are unsurpassed in strength, head size flexibility and integrity. This tank is designed for petroleum products. It is the responsibility of the operator not to exceed the GVW of the unit or DOT and state highway rulings.*

STANDARD TANK FEATURES INCLUDE

- MODIFIED ELLIPTICAL, CANOPY STYLE TANK
- BULKHEAD AND BAFFLE STIFFENERS
- BUILT TO MEET OR EXCEED DOT 406 CODE
- BETTS 16" MANHOLES WITH 10" FILLS & VENTS
- TANK CAPACITY MARKERS IN EACH COMPT.
- ALUMINUM JEEP STYLE FENDERS
- BUMPER HOSE ROLLER
- 14 x 18 x 32 ALUMINUM TOOL BOX
- DIE PRESSED, DEEP DISHED & FLANGED HEADS
- EXPANDED ALUMINUM WALKWAY ON TOP OF TANK
- "VIK" STICKERS & CERTIFICATION, INCLUDING 406 PLATE
- ALUMINUM METER COVER WITH DOORS & LIGHT
- REAR TANK DRAINS WITH SHUTOFF VALVE IN CANOPY
- ALUMINUM BUMPER & LIGHTBAR WITH BETTS LIGHTS
- NOZZLE HOLDER WITH DRAIN
- REAR ALUMINUM LADDER WITH "GRIP STEPS"
- FLEX, SECURITY MOUNTING HARDWARE & OAK SILLS

PUMPING SYSTEM SPECIFICATIONS

9) METER: 2" LC 3" LC M-7 with LCR2_
 PRINTER ROLL PRINTER
 PRESET _____ SPITTER TANK AIR ELIMINATOR

9A) SPECIAL METER CONFIGURATIONS: NONE OTHER

HIGH CAPACITY STRAINER

10) GRAVITY DROP/PUMP SUCTION: NONE 2" 3"
LOCATION _____ ADAPTOR OR CAP:

11) METERED DISCHARGE (QUIK DROP): NONE 2" 3" INLET/OUTLET 3 WAY VALVE METERED
LOCATION: _____ ADAPTOR/CAP:

12) PUMP SPEEDS: 38_GPM (Low Flow) 63_GPM (High Flow)

13) PUMPING SYSTEM: SINGLE DUAL (See Below)

NOTE: All KME trucks are fully Inspected and pump tested and are ready to be put into service upon delivery. Pump testing and meter calibration are included in our standard package.

STANDARD SYSTEM FEATURES INCLUDE:

- 2 1/2" CORKIN PUMP WITH STRAINER
- 3" SUMPS & AIR OPERATED TANK VALVES
- HOSE REEL/PTO INTERLOCK
- 150' OF 1 3/8" GOODYEAR HOSE
- AIR SYSTEM LUBRICATOR
- ALUMINUM PIPING
- SCULLY VALVE WITH TWO SPEED PUMPING CONTROL
- TANK VALVES TIED TO PTO TO PREVENT DRIVING W/ OPEN VALVES
- PHILADELPHIA VALVE HOSE REEL W/ AIR & MANUAL BRAKES
- AIR SHIFT PTO (Cab Controls)
- SCULLY 1 1/2" UNFIL NOZZLE
- METER PRESSURE GAUGE

FOR DUAL PUMPING SYSTEMS ONLY

14) DUAL SYSTEM: COMPARTMENTS DEDICATED TO A PARTICULAR PUMP/METER
 DUAL MANIFOLD SYSTEM
 WHIP (SWING) HOSES WITH DRYBREAKS

FOR BOTTOM LOAD/VAPOR RECOVERY SYSTEMS ONLY

15) BOTTOM LOAD: DIRECT LOADERS (1/COMPT) MANIFOLD
 OPENABLE ADAPTERS NON OPENABLE ADAPTERS
CAPS OR ADAPTORS: CAPS

BOTTOM LOADING/VAPOR RECOVERY CONTINUED:

16) ELECTRONIC OVERFILL PROTECTION: NONE
 SCULLY GO ANYWHERE (SJ6S THERMISTOR, SJ6SO OPTIC)
 SCULLY INTELICHECK
 CIVACON LIBERTY SYSTEM

17) GROUNDING: BRASS LUG SCULLY GROUNDHOG "BALL&BOLT"
 STAINLESS CABLES

18) VAPOR RECOVERY: LOCATION: CAPS OR ADAPTORS

MISCELLANEOUS OPTIONS/EQUIPMENT:

- DOT FLARE TRIANGLES VENTAFIL TUBE
- VINYL DOT HAZMAT SIGNS (4): "FUEL OIL", 1993, 1203,1223 OR OTHER
- FIRE EXTINGUISHER (5LB CAB OR 10LB EXTERNAL W/ BRACKET) 10L ABC
- DOT HAZMAT ALUMINUM FLIP SIGNS: _____
- NOZZLE TUBES
- PAINTING/DECALING (SEE COMMENTS BELOW)

COMMENTS : ALL ALUMINUM PIPING PTO IN REAR
INSTALL GROUNDS ON ALL VICTAULIC'S
USE GASOLINE VICTAULIC'S NOT STANDARD
METHANOL WILL BE THE PRODUCT 6.7 GRAVITY OF PRODUCT .7894
CHANGE WHEEL BASE ON CUSTOMER SUPPLIED CHASSIS TO WEIGHT CALCULATION
ONE 2" BY 4' UGFILL TUBE WITH ADAPTER TO SCULLY NOZZLE 11/4X 4
ROLL PRINTER INSTAED OF SLIP
150' GROUND MANUAL HANNEY MHGR 50-150
2 WORK LIGHTS IN CANOPY ON SWITCH (REVERSE)
2 LED LIGHTS REAR OF TANK (TOP)
ALL LIGHTS WIRED TOGETHER ON SWITCH IN CAB
GEMS DIGITOL READING WITH STAINLESS RODS FOR ALL 3 COMPARTMENTS
3-GEMS #609062 FLOAT TRANSMITTER STAINLESS STEEL
3-GEMS PRECISION DIGITAL EXPLOSION PROOF DISPLAY # PD8-765-7XO-OO
INSTALL ON SPOT CHAINS ON CUSTOMER SUPPLIED CHASSIS